24" & 36" Panel Fans

J&D Manufacturing's 24" and 36" Panel Fans have a rugged frame mount with an efficient motor and a powerful balanced blade that is designed to create comfortable air velocity.

The cushion-mounted maintenance-free bearings and heavy-duty automatic belt tensioning system on belted models make this fan high performing, low maintenance, and a great value.





24" Direct Drive



Features

- Ships fully assembled ready for installation
- Includes heavy-duty hanging chain kit
- Durable cast iron pulleys on belt drive models
- Balanced high-output prop
- Heavy-duty G90 galvanized 18-gauge venturi
- 36" belt drive models include a heavy-duty spring belt tensioning system
- 24" models have a rigid guard motor mount
- 36" models have X-frame that provides superior strength and rigidity compared to angle iron, square or round tube designs
- Wide assortment of optional mounting brackets for wood and steel posts for precise airflow
- Shaft bearings are eccentric locking, pre-lubricated, permanently sealed, rubber mounted for smooth operation and reduced blade fatigue, and are covered by a 3 Year Warranty
- Totally enclosed, maintenance-free, high-efficiency standard motors have completely sealed ball bearings, UL and CUL recognized, and are covered by a 2 Year Warranty
- Gold Star motors have a 3 Year Warranty

▲ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov/product.

24" & 36" Panel Fans

FEATURING .							
GOLD STAR MOTOR				Thrust	Thrust CFM/		
Part#	Size	Ph	Spd	CFM	Watt	Drive	Prop
Single Phase							
VP36D-GS	36"	1	1/Var^	10,710	20.3	Direct	3-Glv
Three Phase							
VP243G-GS	24"	3	1/Var^	10,470	22.3	Direct	3-Glv
VP363D-GS	36"	3	1/Var^	10,590	22.7	Direct	3-Glv

					Thrust	Thrust CFM/		
	Part#	Size	Ph	Spd	CFM	Watt	Drive	Prop
	Single Phase							
	VP24	24"	1	1	5,450	15.4	Direct	3-Alm
**	VP36D	36"	1	1	10,600	20.4	Direct	3-Glv
	VP36	36"	1	1	11,030	19.4	Belt	4-Glv
	VP36DN	36"	1	1	10,530	17.5	Direct	2-Nyl
	VP36N	36"	1	1	10,000	21.4	Belt	2-Nyl
	VP361	36"	1	1	13,000	16.3	Belt	4-Glv
	Three Phase							
	VP243G	24"	3	1	5,740	13.4	Direct	3-Glv
**	VP363D	36"	3	1	10,470	22.3	Direct	3-Glv
	VP363DN	36"	3	1	10,650	19.5	Direct	2-Nyl
	VP3631	36"	3	1	13,080	16.6	Belt	4-Glv
	VP3631-E	36"	3	1	12,500	18.7	Belt	4-Glv
	VP3631N	36"	3	1	12,040	17.8	Belt	2-Nyl


- ** Best sellers of 2018-19
- Variable speed fans require separate variable speed control to adjust fan speed

Bold red text is data based on testing performed by an accredited lab using ANSI/AMCA Standard 230-12

OSHA requires these fans to be mounted a minimum of 7' above the floor $% \left(1\right) =\left(1\right) \left(1\right) \left($

Installation Options

Dire Dri Fai	ve	Belt Drive Fans			
_	_		Part#	Description	
Swi	vel C	ffset l	Post Mountir	ng Bracket	
		Χ	VRSBRPR6P	4"-6" Wood Post, Galv.	
Rigi	d Of	fset Co	olumn Mount	ing Brackets	
		Χ	VRSBRPR3	3" Column, Black Powder Coat	
		Χ	VRSBRPR35	3½" Column, Black Powder Coat	
		Χ	VRSBRPR4	4" Column, Black Powder Coat	
		Χ	VRSBRPR6	6½" Column, Black Powder Coat	
		Χ	VRSBRSQ6	6" Square Column, Painted	
In-I	ine (columr	n Mounting B	rackets	
Χ	Χ	Χ	VRSBRP3	3"-3½" Column, Black Powder Coat & Galv.	
Χ	Χ	Χ	VRSBRP4	4"-4½" Column, Black Powder Coat & Galv.	
Χ	Χ	Χ	VRSBRP4SQ	4"-4½" Sq. Column, Black Powder Coat & Galv.	
Χ	Χ	Χ	VRSBRP5	5"-51/2" Column, Black Powder Coat & Galv.	
Χ	Χ	Χ	VRSBRP6	6"-61/2" Column, Black Powder Coat & Galv.	
Cha	Chain Suspending Kit				
Χ	Χ	Χ	HK211	(3) 72" of Chain, w/Fan to Chain Assem. Hrdwr	







▲ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov/product.